



Bloxide^o

Rust Preventive Weldable Coating

Type Approved by:



BENEFITS

- **Rust Preventative**
 - Protects surfaces & prepared edges from rust
 - Eliminates cleaning of rust prior to welding- saves \$\$
 - Ideal for extended periods of outside steel storage
- **Weldable**
 - Ability to strike welding arc without removal
 - Provides protection for the weld pool
 - Leaves no residue or slag
- **Improves Weld Quality**
 - Reduces porosity & pinholing by protecting the weld pool
 - Assists in achieving X-ray quality welds
- **Safety**
 - Nuclear fabrication industry safe
 - Free from lead, sulfur, zinc, cadmium, mercury, chlorine and other halogens

APPLICATIONS

- Marine and off-shore fabrication, pipes, bridges and steel structures
- Effective on all steels including high tensile, carbon moly and chrome moly
- An excellent primer for paint and other coatings
- Apply by brush, dip or spray with no special equipment or training
- Covers approximately 800 square feet per gallon

Temperature Resistant to 800°F (427°C)

Aluminized Finish

Dry Time: @77°F & 50% rel. hum./Tack Free - 6 hrs.

Recommended Film Thickness:

Wet: 3.0 mil • Dry: .75 mil

Standard Packaging:

12 oz aerosol cans, quarts, gallons,
5 gal. pails and 55 gal. drums



Anti-Heat^o

Heat Absorbing Compound

BENEFITS

- **Absorbs Surface Heat** generated by welding, brazing or soldering
- **Eliminates Heat Damage** by preventing buckling, warping or other distortion of light-gauge metals
- **Creates a Barrier** prohibiting discoloration, blistering or cracking
- **Non-toxic**
- **Harmless to the Skin**
- **Asbestos Free and Odorless**
- **Adheres to** horizontal, vertical and overhead surfaces

How to Use

Fast and easy to apply to all metals. Simply spread it on from the can or directly from a tube which fits in a standard caulking gun. Just wipe off excess with water.

Standard Packaging:

12 oz tubes, quarts, gallons, 5 gallon pails



TEMPIL, 2901 Hamilton Boulevard, South Plainfield, New Jersey 07080
(800) 757-8301 • Tel: (908) 757-8300 • Fax: (908) 757-9273 • E-mail: tempil@tempil.com



FM37044